





Type	Picture	Model	Resolution	Main Features	IRR
Classic Bullet		IPC-HFW1220SP-S3	2Mega	1/2.9" 2M CMOS,ICR,H.264/MJPEG 1080P(1~30fps) , 3.6mm optional,IR 30m,IP67 DC12V/PoE	4,030,000
		IPC-HFW1320SP-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional,IR 30m,IP67 DC12V/PoE	5,310,000
		IPC-HFW1420SP	4Mega	1/3" 4M CMOS,ICR,H.264/MJPEG 4MP(1~20fps),3MP/1080P(1~30fps), 3.6mm lens ,IR 30m,IP67 DC12V/PoE	6,250,000
		IPC-HFW1431SP	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520) & 25/30fps@3M(2304x1296) 3.6mm fixed lens Max IR LEDs Length 30m IP67, PoE	6,980,000
Long IR Range Bullet		IPC-HFW4431EP-S-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.265/H.264,4MP(1~30fps) 3.6mm lens ,IR 40m,Micro SD,IP67,DC12V/PoE	7,560,000
		IPC-HFW4830EP-S	8Mega	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) Max. IR LEDs Length 40m Micro SD memory,IP67, PoE	12,440,000
		IPC-HFW4231B-BAS-H	2MP WDR	1/2.7" 2Megapixel progressive scan CMOS H.265 & H.264 & MJPEG triple stream encoding Max 25/30fps@2M(1920x1080) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens,IR LEDs Length 50m,IP67, PoE	5,220,000
		IPC-HFW4431B-BAS-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS Support H.264&H.265 dual codec 25/30fps@4M(2688x1520),Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens (6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50mMicro SD memory, IP67, PoE	6,220,000
Vari-focal Bullet		IPC-HFW2431RP-VFS	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens,Max IR LEDs Length 30m IP67, PoE	9,390,000
		IPC-HFW2421RP-ZS-IRE6	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m,Micro SD, IP67 DC12V/PoE	8,860,000
		IPC-HFW2431RP-Z-AS-IRE6	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.265+/H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m,Micro SD, IP67 DC12V/PoE	10,610,000











Available on the
App Store



ANDROID APP ON
Google play



Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Bullet		 IPC-HFW5431EP-Z-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264,25/30fps@4Mp(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 2/1Alarmin/out,1/1audioin/out Max. IR LEDs Length 50m, Micro SD memory, IP67, PoE	11,070,000
		 IPC-HFW8331EP-Z	3Mega WDR	1/2.8" 3Megapixel progressive scan STARVIS™ CMOS H.265&H.264,50/60fps@3M(2048×1536) WDR(140dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m MicroSDmemory,IP67,IK10,PoE+	28,910,000
		  IPC-HFW81230EP-Z	12Mega	1/1.7" 12Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 20fps@12M(4000×3000),25/30fps@4K(3840×2160) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC 4.1mm ~16.4mm motorized lens Max. IR LEDs Length 50m Micro SD memory,IP67,IK10,PoE+	Call
Box Network		 IPC-HF5431EP-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.264&H.265,25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2/1 Alarm in/out, 1/1 audio in/out(Built-in Mic) Auto back focus(ABF),Micro SD memory, PoE	9,330,000
		 IPC-HF8232FP	2Mega Starlight	1/1.9" 2Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 50/60fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Auto back focus(ABF), Micro SD memory, PoE	24,290,000










Available on the
App Store



ANDROID APP ON
Google play



Type	Picture	Model	Resolution	Main Features	IRR
Mini Dome		IPC-HDBW4431FP	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 20m Micro SD memory, IP67, IK10, PoE	10,390,000
Vandal Dome		IPC-HDBW1220EP-0360B-S3	2Mega	1/2.9" 2M CMOS,ICR,H.264/MJPEG 1080P(1~30fps) , 3.6mm optional,IR 30m,IP67,IK10 DC12V/PoE	4,100,000
		IPC-HDBW1320EP-0360B-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional, IR 30m,IP67,IK10 DC12V/PoE	5,430,000
		IPC-HDBW1420EP-0360B	4Mega	1/3" 4M CMOS,ICR,H.264/MJPEG 4MP(1~20fps),3MP/1080P(1~30fps), 3.6mm lens IR 30m,IP67,IK10 DC12V/PoE	7,250,000
		IPC-HDBW1431EP-0360B	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) 3.6mm fixed lens Max IR LEDs Length 30m IP67, PoE	7,250,000
Long IR Range Eyeball		IPC-HDW4231E-AS-H	2Mega WDR	1/2.7" 2Megapixel progressive scan CMOS H.265 & H.264 & MJPEG triple stream encoding Max 25/30fps@2M(1920×1080) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens,IR LEDs Length 50m,IP67, PoE	5,060,000
		IPC-HDW4421EP-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.264,4MP(1~20fps) 3.6mm lens,IR 50m,IP66 DC12V/PoE	6,710,000
		 IPC-HDW4421EMP-AS-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.264,4MP(1~20fps) 3.6mm lens ,IR 50m,Built-in Mic, Mirco SD,IP67 DC12V/PoE	7,040,000
		 IPC-HDW4431EMP-AS-0360B	4Mega WDR	1/3" 4M CMOS,ICR,WDR (120dB) H.265/H.264,4MP(1~30fps) 3.6mm lens,IR 50m,Built-in Mic, Mirco SD,IP67 DC12V/PoE	8,860,000
		 IPC-HDW4431EP-AS-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS Support H.264&H.265 dual codec 25/30fps@4M(2688×1520),Smart Detectionsupported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens (6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50mMicro SD memory, IP67, PoE	6,280,000
		 IPC-HDW4830EMP-AS	8Mega	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) IR LEDs Length 40m Micro SD memory,IP67, PoE	12,440,000













Available on the
App Store



ANDROID APP ON
Google play



Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Dome		 IPC-HDBW2421RP-ZS	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.264/MJPEG,4MP(1~20fps),3MP/1080P(1~30fps) 2.7-12mm motorized lens IR 30m, Micro SD, IP67, IK10 DC12V/PoE	8,450,000
		 IPC-HDBW2431RP-ZAS	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.265+/H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m, Micro SD, IP67 DC12V/PoE	10,490,000
		 IPC-HDBW2431RP-VFS	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens, Max IR LEDs Length 30m IP67, PoE	9,390,000
		 IPC-HDBW5231EP-Z	2Mega WDR	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 50/60fps@1080(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 1/1 Alarm in/out, 1/1 audio in/out IR LEDs Length50m, Micro SD memory, IP67, IK10, PoE	14,640,000
		 IPC-HDBW5431EP-Z	2Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264,25/30fps@4Mp(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m, IP67, IK10, PoE, Micro SD card	18,390,000
		 IPC-HDBW5431EP-Z-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264,25/30fps@4Mp(2688x1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 2/1Alarmin/out,1/1audioin/out Max. IR LEDs Length 50m, Micro SD memory, IP67, PoE	10,980,000
		 IPC-HDBW8232EP-Z	2MP Starlight WDR	1/1.9" 2Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 50/60fps@1080P(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 4.1mm ~16.4mm motorized lens Max.IRLEDsLength50m, MicroSDmemory, IP67, IK10, POE	35,260,000
		 IPC-HDBW8331EP-Z	3Mega WDR	1/2.8" 3Megapixel progressive scan STARVIS™ CMOS H.265&H.264,50/60fps@3M(2048x1536) WDR(140dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m MicroSDmemory, IP67, IK10, PoE+	28,910,000
		 IPC-HDBW81230EP-Z	12Mega	1/1.7" 12Megapixel progressive scan STARVIS™ H.265&H.264 triple-stream encoding 20fps@12M(4000x3000),25/30fps@4K(3840x2160) 4.1mm ~16.4mm motorized lens Max. IR LEDs Length 50m Micro SD memory, IP67, IK10, PoE+	Call



Available on the
App Store



GET IT ON
Google play



Type	Picture	Model	Resolution	Main Features	IRR
Indoor PTZ		SD22204T-GN	2Mega 4X	1/2.7" 2Megapixel CMOS Powerful 4x optical zoom Support Triple-streams encoding WDR, Day/Night(ICR), Ultra DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IVS Support PoE Max 100°/s pan speed , IP66, IK10	8,990,000
Speed Dome		SD49225T-HN	2Mega 25X	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology Support H.265&H.264 Triple-streams encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P IVS, Support PoE+ IR distance up to 100m ,IP66	26,160,000
		SD59430U-HNI	4Mega 30X	1/3" 4Megapixel CMOS Powerful 30x optical zoom H.265 Encoding Max. 25/30fps@4M/3M, 25/30/50/60fps@1080P Auto-tracking and IVS Support PoE+ ,IR distance up to 100m IP66	54,950,000
		SD6C225U-HNI	2Mega 25x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology,H.265 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P Auto-tracking and IVS, IR distance up to 150m,IP66	39,530,000
		SD6C430U-HNI	4Mega 30X	1/3" 4Megapixel CMOS Powerful 30x optical zoom,H.265 Encoding Max. 25/30fps@4M/3M, 25/30/50/60fps@1080P Auto-tracking and IVS,IR distance up to 100m,IP66	58,070,000
		SD6AE240V-HNI	2Mega 40x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 40x optical zoom, Starlight technology H.265 Encoding,Max. 50/60fps@1080P Support Hi-PoE,IR distance up to 200m,IP67 , IK10	114,680,000







Available on the
App Store










MADE WITH
Google play



Type	Picture	Model	Resolution	Main Features	IRR
Panoramic		IPC-PSD81602-A360	8x2MP Multi-Sensor Panoramic +PTZ Camera	Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS PTZ: One 1/1.9" 2Megapixel progressive scan CMOS H.265/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view Day/Night(ICR), 3DNR, AWB, AGC, BLC, Smart tracking Intelligent Function, Micro SD memory, IP67, IK10	Call
		IPC-PBW8601P	3x2 Mega	Three 1/2.8" 2Megapixel progressive scan STARVIS. CMOS H.265/H.264 triple-stream encoding Max 25/30fps@4096x832 Support 180-degree panoramic view Smart detection ,Intelligent Function Max. IR LEDs length 30m Micro SD memory, IP67, IK10, PoE+	Call
		IPC-EBW81200P	4K	12Mega	1/2.3" 12Megapixel Exmor R CMOS H.264+/H.264 encoding Max 15fps@12M(4000x3000), 30fps@3M 1.57mm /F 2.2 lens Max> IR LEDs length 10m, Audio In/Out 1/1 Micro SD memory, IP67, IK10, PoE
Cube		IPC-K35AP	3Mega	1/3" 3Megapixel progressive CMOS H.264& MJPEG dual-stream encoding 20fps@3M(2304x1296)&25/30fps@2M (1920x1080) 100° horizontal view angle IR Distant 10m Easy4ip cloud support Micro SD card slot, up to 128GB Alarm in/out, PIR DC12V, PoE	5,540,000



Type	Picture	Model	Main Features	IRR	
Compact 1U 1HDD		NVR1A08HS	8 Channel H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6Mp resolution preview&playback HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	3,750,000	
Compact 1U 1HDD		NVR4108HS-4KS2	8 Channel H.265/H.264 codec decoding Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	8,110,000	
1U 2HDD		NVR4216-4KS2	16/32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	12,690,000	
		NVR4232-4K-S2		14,250,000	
1.5U 4HDD		NVR4432-4K-S2		H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	19,460,000
		NVR5464-4K-S2	38,710,000		
2U 8HDD		NVR4832-4K-S2	32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down		32,150,000
		NVR5864-4K-S2			52,800,000
		NVR608-32-4KS2	384Mbps, Max 12MP, 16ch 1080P decoding, H.265/H.264, 1 VGA/2 HDMI(3840x2160), 2 RJ45(1000M), 4 USB(2USB3.0), 1/1ch audio in/out, 8 HDD(6TB each), 1 eSATA, 16/8 alarm in/out, fisheye dewarp, Smart Track, IVS(optional), face detection, RAID0/1/5/6/10/50/60, N+M, ANPR, thermal	Call	
		NVR608-64-4KS2		Call	



Available on the
App Store



ANDROID APP ON
Google play



Type	Picture	Model	Main Features	IRR
4-Port PoE Switch (Unmanaged)		PFS3005-4P-58	Two-layer PoE Ethernet switch MAC auto study and aging, MAC address list capacity is 1K Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation. Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.	2,680,000
8-Port PoE Switch (Unmanaged)		PFS3110-8P-96	Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Support IEEE802.3af, IEEE802.3at standard Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Industrial wide temperature design	6,220,000
16-Port PoE Switch		PFS4218-16ET-240	Layer 2 management PoE switch PoE budget: 240W Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission PoE management, PoE Setting/Event Statistics/Green PoE Search and upgrade via ConfigTool Support Web management High lightning protection design Non-blocking video transmission	19,400,000
24-Port PoE Switch		PFS4226-24ET-360	Layer 2 management PoE switch PoE budget: 240W Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission PoE management, PoE Setting/Event Statistics/Green PoE Search and upgrade via ConfigTool Support Web management High lightning protection design Non-blocking video transmission	23,180,000
PoE Extender		PFT1300	Support passive PoE cascade power supply and Ethernet data exchange able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m 1*RJ45 10/100M PoE power supply input; 1*RJ45 10/100M supply power for IP Cam; 1*RJ45 10/100M supply power for the next extender	Call
Ultra-HD Network Video Decoder		NVD0405DH-4K	H.265/H.264/MPEG4 video decoding 4ch@12M/4ch@4K/16ch@1080P/64ch@D1 decoding ability 1ch HDMI input, 4ch HDMI/VGA/BNC output, HDMI support Ultra HD 4K output Support up to 4 video-wall display units, support configuration of 1x1, 2x1, 2x2 Support audio, alarm, bi-directional talk, RS485	Call
Network Keyboard		NKB1000	Keyboard to Control: Dahua High Speed Dome Dahua Standalone DVR Dahua Network High Speed Dome Network Video Server Connection	15,250,000






Available on the App Store



GET IT ON Google play



Type	Picture	Model	Main Features	IRR
Lens		PLZ1040-D	Focal length:2.7-12mm Aperture:F1.6 Focus:Manual Zoom:Manual Iris:DC-Iris	2,650,000
		PLZ20C0-D	Focal length:3.7-16mm Aperture:F1.5 Focus:Manual Zoom:Manual Iris:DC-Iris	call
		PLZ21C0-P	Focal length:10.5-42mm Aperture:F1.5 Focus:Manual Zoom:Manual Iris:DC-Iris	call



Available on the
App Store



GET IT ON
Google play

