











Type	Picture	Model	Resolution	Main Features	IRR
Bullet		HAC-HFW1000RM	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 20m, Smart IR 2.8mm fixed lens	1,440,000
Classic Bullet		HAC-HFW1000S	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 20m, Smart IR 2.8mm fixed lens	1,680,000
		HAC-HFW1200S	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	2,370,000
		HAC-HFW1220S	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	2,610,000
Classic Bullet		HAC-HFW1200T	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 20m, Smart IR 3.6mm fixed lens	2,190,000
		HAC-HFW1400T	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps 25/30fps@1080P,720P ICR, IP67,DWDR Max. IR Led length: 20m, Smart IR	3,270,000
Long IR Range Bullet		HAC-HFW2231E	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 40m, Array LED, Smart IR 3.6mm fixed length	5,180,000
		HAC-HFW1200B	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Smart IR 3.6mm fixed lens	2,780,000
		HAC-HFW1400B	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps ,25/30fps@1080P,720P ICR, IP67,DWDR Max. IR Led length: 50m, Smart IR	4,060,000
		HAC-HFW1220D	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 80m, Smart IR 3.6mm fixed lens	3,170,000
		HAC-HFW2231D	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30 fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 80m, Array LED, Smart IR 3.6mm fixed length	5,760,000

Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Bullet		HAC-HFW1220R-VF-IRE6	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P , ICR, IP67 Max. IR Led length: 60m, Array LED, Smart IR manual vari-focal lens	4,350,000
		HAC-HFW2221R-Z-IRE6	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 60m, Array LED, Smart IR motorized lens	7,260,000
		HAC-HFW2231R-Z-IRE6	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30fps@720P, ICR, IP67,120db Ture WDR Max. IR Led length: 60m, Array LED, Smart IR motorized lens	9,180,000
		HAC-HFW1400R-VFS-IRE6	4MP	Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 60m, Smart IR IP67, DC12V	6,130,000
Classic Dome		HAC-HDW1000M	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	1,440,000
		HAC-HDW1200M	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	2,150,000
Long IR Range Eyeball		 HAC-HDW1200EM-A	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	2,520,000
		 HAC-HDW1220EM-A	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	2,770,000
		 HAC-HDW2221EM-A	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length Bulit-in Mic, All Metal	4,350,000
		HAC-HDW2231EM	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30fps@720P, ICR, IP67, 120db Ture WDR Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length Bulit-in Mic, All Metal	5,260,000
		 HAC-HDW1400EM-A	4MP WDR	1/3" 4Megapixel CMOS, 4MP 25/30fps 25/30fps@1080P,720P ICR, IP67,DWDR Max. IR Led length: 50m, Smart IR Bulit-in Mic, All Metal	3,650,000

Type	Picture	Model	Resolution	Main Features	IRR
Vandal Dome		HAC-HDBW1220R-VF	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P , ICR, IP67, IK10 Max. IR Led length: 30m, Array LED, Smart IR manual vari-focal lens	4,000,000
		HAC-HDBW2221R-Z	1080P WDR	1/2.7" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, ICR, IP67, IK10, 120db True WDR Max. IR Led length: 30m, Array LED, Smart IR motorized lens	7,370,000
		HAC-HDBW2231R-Z	Starlight 1080P	Starlight, 120dB true WDR, 3DNR Max 30fps@1080P HD and SD output switchable motorized lens Max. IR length 30m, Smart IR IP67, IK10, DC12V	8,860,000
		HAC-HDBW1400R-VFS	4MP	Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 30m, Smart IR IP67, IK10, DC12V	6,130,000
Vari-focal Bullet		HAC-HFW3231E-Z	Starlight 1080P	1/2.8" 2.1Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Star Light, 120dB True WDR ICR, IP67 Max. IR Led length: 50m, Smart IR 2.7-12mm auto-iris motorized lens DC12V/AC24V, audio in, alarm in & out Tri-output	11,500,000
Vari-focal Dome		HAC-HDBW3231E-Z	Starlight 1080P	1/2.8" 2.1Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Star Light, 120dB True WDR ICR, IP67, IK10 Max. IR Led length: 50m, Smart IR 2.7-12mm auto-iris motorized lens DC12V/AC24V, audio in, alarm in & out Tri-output	11,500,000
Vari-focal Bullet		HAC-HFW3802E-Z	8MP WDR	1/2" 8Megapixel progressive scan CMOS 3x optical motorized zoom lens Max. 15fps@3840x2160 120db true WDR, 2D&3D NR Max.100m IR distance, smart IR IP67/IK10 ingress protection Dual voltage input(DC 12v±25%/AC 24V±25%) DC12V voltage output Up to 500m transmission with RG59 coaxial cable	17,710,000
Vari-focal Dome		HAC-HDBW3802E-Z	8MP WDR	1/2" 8Megapixel progressive scan CMOS 3x optical motorized zoom lens Max. 15fps@3840x2160 120db true WDR, 2D&3D NR Max.50m IR distance, smart IR IP67&IK10 ingress protection Dual voltage input(DC 12v±25%/AC 24V±25%) DC12V voltage output Up to 500m transmission with RG59 coaxial cable	17,710,000
Pinhole Camera		HAC-HUM3201B	2MP Starlight	Starlight, 120dB true WDR, 3DNR Max 30fp@1080P HD and SD output switchable 3.6mm fixed lens (2.8mm optional) DC12V	4,630,000
MotionEye Camera		HAC-HUM1220A-PIR	1080P	Max 30fps@1080P HD and SD output switchable 2.8mm fixed lens 12m/100°detecting range/angle Two level detection sensitivity adjustable Built-in tamper switch DC12V	3,340,000

Type	Picture	Model	Resolution	Main Features	IRR
Indoor PTZ		SD22204I-GC	1080P 4x PTZ	1/2.7" 2Megapixel CMOS Powerful 4x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IP66, IK10	8,280,000
Speed Dome		SD49225I-HC	1080P 25x Starlight IR PTZ	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology 120dB true WDR, 3D DNR Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 100m IP66	27,060,000
		SD59430I-HC	4MP 30x IR PTZ	1/3" 4Megapixel CMOS Powerful 30x optical zoom 120dB true WDR, 3D DNR Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P IR distance up to 100m IP66	45,540,000












Available on the
App Store



GET IT ON
Google play



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid XVR4104HS-S2	4CH:1080N/720P (1~25/30fps) 8/16CH:1080N(1~12fps)/720P(1~15fps) Support HDCVI/AHD/TVI/CVBS/IP video inputs 4+1: each channel up to 2MP , 8+2/16+2:each channel up to 5MP Long transmission distance over coax cable & Coax Audio 1 HDMI/1 VGA, 1 Audio in/1 Audio out,1 RJ45(100M),2 USB Support 1 SATA HDD, up to 8TB	3,740,000
		AOC Penta-brid XVR4108HS-S2		5,130,000
		AOC Penta-brid XVR4116HS-S2		8,920,000
1U 2HDD		AOC Penta-brid XVR4216A-S2	16ch 1080N(1~12fps)/720P(1~15fps) 1 HDMI/1 VGA,4 Audio in/1 Audio out,16 Alarm in/3 Alarm out,1 RJ45(100M),1 RS485,2 USB,2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+2 IP camera input,up to 5Mp Long transmission distance over coax cable & Coax Audio	13,520,000
		Tribrid HCVR4232AN-S3	32ch 720P 12/15fps per channel 1U Case,1 HDMI/1 VGA, 1 RJ45(100M), 1 Audio in/1 Audio out, 1 RS485,2 USB, 2 HDD, Tribrid(Analog&HD-CVI self-adaptive, 16 IP camera input,up to 5Mp)	23,000,000
Compact 1U 1HDD		AOC Penta-brid XVR5104HS-S2	4/8 ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2/8+4 Channel, each channel up to 5MP Long transmission distance over coax cable & Coax Audio	5,450,000
		AOC Penta-brid XVR5108HS-S2		9,060,000
1U 2HDD		AOC Penta-brid New XVR5216AN-S2	16ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),1 Audio in/1 Audio out,1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+8 IP camera input,up to 5Mp) Long transmission distance over coax cable & Coax Audio	17,950,000
		AOC Penta-brid XVR5216A-S2	16ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/3 Alarm out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+8 IP camera input,up to 5Mp) Long transmission distance over coax cable & Coax Audio	19,440,000
AOC=Audio Over Coaxial		Tribrid=CVI/CVBS/IP	Penta-brid=CVI/AHD/TVI/CVBS/IP	

Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid XVR5104HS-4M	4MP/3MP(1~15fps), 1080P@25/30fps, 720P@50/60fps 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2 Channel, each channel up to 5MP, Coax Audio	7,880,000
		AOC Penta-brid XVR5108HS-4KL	8 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP)8+4 Channel, each channel up to 8MP, Coax Audio	11,800,000
1U 2HDD		AOC Penta-brid XVR5216AN-4KL	16 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2USB,2HDD (CVBS/HD-CVI/AHD/TVI/IP)16+8 Channel, each channel up to 8MP, Coax Audio	22,690,000
1.5U 4HDD		AOC Penta-brid XVR5416L	16ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M), 4 Audio in/1 Audio out,8/16/16 Alarm in/6 Alarm out, 1 RS485,3 USB, 4 HDD, Penta-brid(CVBS/HD- CVI/AHD/TVI/IP) self-adaptive,16+8/16 IP camera input, up to 5Mp)	32,900,000
2U 8HDD		AOC Penta-brid XVR8816	16ch 4M 10/15 fps & 1080P 25/30 fps per channel 2 HDMI/1 VGA,2 RJ45(1000M), 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Analog&HD-CVI-AHD-TVI self- adaptive,16+48 IP camera input,up to 12Mp 384Mbps) People Counting , HeatMap ,	71,350,000
1U 1HDD		AOC Penta-brid XVR5232AN-S2	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,32 Channel, each channel up to 5MP)	30,920,000
1.5U 4HDD		AOC Penta-brid XVR5432L	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,4 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,32 Channel, each channel up to 5MP)	45,490,000
2U 8HDD		AOC Penta-brid XVR5832S	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M), 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 8 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 Channel, each channel up to 5MP)	55,200,000
1.5U 4HDD		AOC Penta-brid XVR7416L	16ch 1080P 25/30fps per channel, 720P realtime 2 HDMI/1 VGA,1 RJ45(1000M), 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 4 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,16+8 IP camera input,up to 5Mp	33,640,000
2U 8HDD		HCVR8816S-S3	16ch 1080P 25/30fps per channel 2 HDMI/1 VGA,2 RJ45(1000M), 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Analog&HD-CVI-AHD self- adaptive,16+48 IP camera input,up to 12Mp 256Mbps) People Counting , HeatMap ,	45,860,000

AOC=Audio Over Coaxial

Tribrid=CVI/CVBS/IP

Penta-brid=CVI/AHD/TVI/CVBS/IP



Available on the
App Store



GET IT ON
Google play



Type	Picture	Model	Main Features	IRR
Keyboard		NKB1000	Dahua Standalone DVR Dahua Network High Speed Dome Network Video Server Connection	19,550,000
HDCVI Video Converter		TP2105	Self-adaptive output HDCVI, HDMI, VGA, CVBS signal Lossless real time non-compression transmission Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s Fully enclosed dustproof design	4,000,000
HDCVI Distributor		TP2600	Support 1/3 channel In/Out Lossless non-compression transmission Support video format as 25/30/50/60fps@720P & 25/30fps@1080P UPnP, easy installation LED indicators	4,570,000
UTC Controller		PFM820	Support different formats(HDCVI/AHD/HDTVI/CVBS)switch,which is to satisfy requirements of different storage deviceenvironments for clients.	910,000
Wall mount		PFB203W	HDBWxxR-Z/VF/E/F,HDWxxR-Z/VF/EM/E/S ,EB Material: Aluminum Wall Mount Bracket	560,000
Junction box		PFA121	HFwxxEZ/E Series Material: Aluminum IP66 Junction Box	970,000
		PFA134	HFwxS ,HFwxT,HFwxSL,HFwxRM,HFwxR Series Material: Aluminum IP66 Junction Box	400,000
		PFA135	HFwxR-Z/VF,HFwxB,HFwxD Series Material: Aluminum IP66 Junction Box	320,000
		PFA137	HDBWxxR-Z/VF , HDWxxR-Z,SD22 Series Material: Aluminum IP66 Junction Box	400,000
		PFA139	HDBWxxF , HDWxxEM Series Material: Aluminum IP66 Junction Box	390,000
Pole mount		PFA152-E	PFB203W,PFA121,PFA134,PFA135,PFA137+ PFA152-E Pole mount Material: Aluminum	1,290,000
Passive HDCVI Balun		PFM800-4M	1 Channel Passive HDCVI BalunReal-time transmission over UTP CAT5E/6 cable. Passive, no need for power supply. With female BNC connector, and pluggable screw terminal connections.	320,000
Isolator		PFM790	Power supply isolator, to solve the HDCVI image interference caused by power supply effectively	390,000
		PFM791	HD video isolator, to solve the HDCVI image interference caused by ground loops effectively	480,000



Available on the
App Store



GET IT ON
Google play

