
























Type	Picture	Model	Resolution	Main Features	IRR
Classic Dome		HAC-HDW1000M	720P	1/4" 1Megapixel CMOS 720P, ICR, IP67 Max. IR Led length: 30m, Smart IR 2.8mm fixed lens	2,240,000
		HAC-HDW1200M	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens	3,200,000
Pro Series		 HAC-HDW1200EM-A	1080P	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	3,950,000
		 HAC-HDW1220EM-A	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67 Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed lens Bulit-in Mic, All Metal	3,770,000
		HAC-HDW2231EM	1080P WDR	1/2.8" 2.1Megapixel CMOS Starlight 25/30fps@1080P, 25/30fps@720P, ICR, IP67, 120db Ture Max. IR Led length: 50m, Array LED, Smart IR 3.6mm fixed length, All Metal	7,450,000
		 HAC-HDW1400EM-A	4MP	1/3" 4Megapixel CMOS, 4MP 25/30fps 25/30fps@1080P,720P ICR, IP67, Max. IR Led length: 50m, Smart IR Bulit-in Mic, All Metal	5,330,000
Lite H.265 Series		HAC-HDBW1220R-VF	1080P	1/2.9" 2Megapixel Exmor CMOS 1080P , ICR, IP67, IK10 Max. IR Led length: 30m, Array LED, Smart IR manual vari-focal lens	6,770,000
		HAC-HDBW2231R-Z	Starlight 1080P	Starlight, 120dB true WDR, 3DNR Max 30fps@1080P HD and SD output switchable motorized lens Max. IR length 30m, Smart IR IP67, IK10, DC12V	Call
		HAC-HDBW1400R-VFS	4MP	Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 30m, Smart IR, IP67, IK10, DC12V	8,240,000
Vari-focal Dome		HAC-HDBW3802E-Z	8MP WDR	1/2" 8Megapixel progressive scan CMOS 3x optical motorized zoom lens Max. 15fps@3840x2160 120db true WDR, 2D&3D NR Max.50m IR distance, smart IR, IP67&IK10 Dual voltage input(DC 12v±25%/AC 24V±25%)	15,400,000



Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid <a href="#">XVR4104HS-S2</a>	4CH:1080N/720P (1~25/30fps) 8/16CH:1080N(1~12fps)/720P(1~15fps) Support HDCVI/AHD/TVI/CVBS/IP video inputs 4+1: each channel up to 2MP , 8+2/16+2:each channel up to 5MP & <b>Coax Audio</b> , 1 HDMI/1 VGA, 1 Audio in/1 Audio out,1 RJ45(100M),up to 8TB	6,150,000
		AOC Penta-brid <a href="#">XVR4108HS-S2</a>		7,900,000
		AOC Penta-brid <a href="#">XVR4116HS-S2</a>		13,700,000
1U 1HDD		AOC Penta-brid XVR4216A-S2	16ch 1080N(1~12fps)/720P(1~15fps) 1 HDMI/1 VGA,,4 Audio in/1 Audio out,16 Alarm in/3 Alarm out,1 RJ45(100M),1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+2 IP camera input,up to 5Mp & <b>Coax Audio</b>	19,700,000
Compact 1U 1HDD		AOC Penta-brid <a href="#">XVR5104HS-S2</a>	4/8 ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2/8+4 Channel, each channel up to 5MP Long transmission distance over coax cable & <b>Coax Audio</b>	8,120,000
		AOC Penta-brid <a href="#">XVR5108HS-S2</a>		12,880,000
1U 2HDD		Penta-brid XVR5216AN-S2	16ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/3 Alarm out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,16+8 IP camera input,up to 5Mp) Long transmission distance over coax cable & <b>Coax Audio</b>	23,640,000
		AOC Penta-brid <a href="#">XVR5232AN-S2</a>	32ch 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 IP camera input,up to 5Mp) Long transmission distance over coax cable & <b>Coax Audio</b>	41,500,000
		AOC Penta-brid <a href="#">XVR5208AN-4KL</a>	8ch 4K(1~7fps) ,5MP(1~12fps) 4M-N/1080P(1~15fps);1080N/720P(1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2 USB, 2 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,8+4 IP camera input,up to 8Mp) Long transmission distance over coax cable & <b>Coax Audio</b>	23,300,000
AOC=Audio Over Coaxial		Tribrid=CVI/CVBS/IP	Penta-brid=CVI/AHD/TVI/CVBS/IP	

Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		AOC Penta-brid  <a href="#">XVR5104HS-4M</a>	4MP/3MP(1~15fps), 1080P@25/30fps, 720P@50/60fps 1 HDMI/1 VGA,1 RJ45(100M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP) 4+2 Channel, each channel up to 5MP,Coax Audio	10,800,000
		AOC Penta-brid  <a href="#">XVR5108HS-4KL</a>	8 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),1 Audio in/1 Audio out, 1 RS485,2USB,1HDD (CVBS/HD-CVI/AHD/TVI/IP)8+4 Channel, each channel up to 8MP,Coax Audio	16,720,000
1U 2HDD		AOC Penta-brid  <a href="#">XVR5216AN-4KL</a>	16 ch 4K(1~7fps),5MP(1~12fps),4MP(1~15fps),1080P/720P (1~25/30fps) 1 HDMI/1 VGA,1 RJ45(1000M),4 Audio in/1 Audio out, 1 RS485,2USB,2HDD (CVBS/HD-CVI/AHD/TVI/IP)16+8 Channel, each channel up to 8MP,Coax Audio	31,600,000
2U 8HDD		AOC Penta-brid  XVR8816	16ch 4M 10/15 fps & 1080P 25/30 fps per channel 2 HDMI/1 VGA,2 RJ45(1000M), 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Anolog&HD-CVI-AHD-TVI self- adaptive,16+48 IP camera input,up to 12Mp 384Mbps) People Counting , HeatMap ,	Call
1U 1HDD		AOC Penta-brid  XVR5232AN-S2	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,4 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,32 Channel, each channel up to 5MP )	41,500,000
1.5U 4HDD		AOC Penta-brid  XVR5432L	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M),4 Audio in/1 Audio out,16 Alarm in/6 Alarm out,1 RS485,3 USB,4 HDD,Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,32 Channel, each channel up to 5MP )	80,600,000
2U 8HDD		AOC Penta-brid  XVR5832S	32ch 1080P 12/15fps per channel, 720P realtime 2 HDMI/1 VGA/1 TV,2 RJ45(1000M), 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 8 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self-adaptive,32 Channel, each channel up to 5MP )	89,000,000
1.5U 4HDD		AOC Penta-brid  XVR7416L	16ch 1080P 25/30fps per channel, 720P realtime 2 HDMI/1 VGA,1 RJ45(1000M), 4 Audio in/1 Audio out,16 Alarm in/6 Alarm out, 1 RS485,3 USB, 4 HDD, Penta-brid(CVBS/HD-CVI/AHD/TVI/IP) self- adaptive,16+8 IP camera input,up to 5Mp	59,800,000
2U 8HDD		AOC Penta-brid  HCVR8816	16ch 1080P 25/30fps per channel 2 HDMI/1 VGA,2 RJ45(1000M), 16 Audio in/1 Audio out, 16 Alarm in/6 Alarm out, 2 RS485,2 USB, 8 HDD,eSATA,Tribrid(Anolog&HD-CVI-AHD self- adaptive,16+48 IP camera input,up to 12Mp 256Mbps) People Counting , HeatMap ,	121,000,000
AOC=Audio Over Coaxial		Tribrid=CVI/CVBS/IP	Penta-brid=CVI/AHD/TVI/CVBS/IP	

Type	Picture	Model	Main Features	IRR
Alarm Box		<b>NEW</b> DHI-ARB1606	Support through RS485 access to the back-end storage Support 16ch Alarm In/6ch Alarm Out interface Support 2-bit DIP switch (0/1) to determine the different alarm box access; Max support 4 alarm boxes having access to the back-end storage device Linked conguration alarm to DVR	3,740,000
HDCVI Distributor		TP2600	Support 1/3 channel In/Out Lossless non-compression transmission Support video format as 25/30/50/60fps@720P & 25/30fps@1080P UPnP, easy installation LED indicators	3,970,000
UTC Controller		PFM820	Support different formats(HDCVI/AHD/HDTVI/CVBS)switch,which is to satisfy requirements of different storage deviceenvironments for clients.	Call
Wall mount		PFB203W	HDBWxxR-Z/VF/E/F,HDWxxR-Z/VF/EM/E/S ,EB Material: Aluminum Wall Mount Bracket	940,000
Junction box		PFA121	HFWxxEZ/E Series Material: Aluminum IP66 Junction Box	1,600,000
		PFA134	HFWxxS ,HFWxxT,HFWxxSL,HFWxxRM,HFWxxR Series Material: Aluminum IP66 Junction Box	670,000
		PFA135	HFWxxR-Z/VF,HFWxxB,HFWxxD Series Material: Aluminum IP66 Junction Box	530,000
		PFA137	HDBWxxR-Z/VF , HDWxxR-Z,SD22 Series Material: Aluminum IP66 Junction Box	670,000
		PFA139	HDBWxxF , HDWxxEM Series Material: Aluminum IP66 Junction Box	730,000
Pole mount		PFA152-E	PFB203W,PFA121,PFA134,PFA135,PFA137+ PFA152-E Pole mount Material: Aluminum	2,140,000
Passive HDCVI Balun		<b>NEW</b> PFM800-4M	1 Channel Passive HDCVI BalunReal-time transmission over UTP CAT5E/6 cable. Passive, no need for power supply. With female BNC connector, and pluggable screw terminal connections.	530,000
POC Transceiver		PFM810	Power supply: Input voltage DC24-36V, can provide DC12V 9W(max) power supply to remote cameras, simplify engineering wiring Transmission distance: 400m (max) Main functions: Use single coaxial cable real-time transmit 1-ch HD video signal and 1-ch DC power	2,000,000