












Type	Picture	Model	Resolution	Main Features	IRR
EZ-IP		IPC-B1A20	2Mega	1/2.9" 2Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6mm optional) Max IR LEDs Length 30m IP67, PoE	6,580,000
		IPC-B1A30	3Mega	1/3" 3Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm 6mm optional) Max IR LEDs Length 30m, IP67, PoE	7,500,000
Lite Series		DH-IPC-HFW1230SP	2MP	1/2.7" 2M CMOS,ICR, H.265 & H.264 1080P(1~30fps) , 2.8 mm (3.6 mm optional),IR 30m,IP67 DC12V/PoE	6,910,000
		IPC-HFW1320SP-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional,IR 30m,IP67 DC12V/PoE	8,470,000
		IPC-HFW1431SP	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520) &25/30fps@3M(2304x1296) 3.6mm fixed lens Max IR LEDs Length 30m IP67, PoE	11,970,000
Eco-savvy		IPC-HFW4231B-BAS-H	2MP WDR	1/2.7" 2Megapixel progressive scan CMOS H.265 & H.264 & MJPEG triple stream encoding Max 25/30fps@2M(1920x1080) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens,IR LEDs Length 50m,IP67, PoE	9,520,000
		IPC-HFW4431B-BAS-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS Support H.264&H.265 dual codec 25/30fps@4M(2688x1520),Smart Detectionsupported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens (6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50mMicro SD memory, IP67, PoE	11,100,000
Vari-focal Bullet		DH-IPC-HFW2231TP-VFS	2Mega	1/2.8" 2Megapixel progressive Starvis™ CMOS H.265 & H.264 dual-stream encoding 25/30fps@1080P(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens Max IR LEDs Length 60m IP67, IK10(optional), PoE+	17,980,000
		IPC-HFW2431T-ZS	4Mega	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens Max IR LEDs Length 60m IP67, IK10(optional), PoE+	17,670,000
		IPC-HFW2431RP-Z-AS-IRE6	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.265+/H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m,Micro SD, IP67 DC12V/PoE	17,400,000






Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Bullet		 IPC-HFW5431EP-Z-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264,25/30fps@4Mp(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 2/1Alarmin/out,1/1audioin/out Max. IR LEDs Length 50m, Micro SD memory, IP67, PoE	21,370,000
		 IPC-HFW8331EP-Z	3Mega WDR	1/2.8" 3Megapixel progressive scan STARVIS™ CMOS H.265&H.264,50/60fps@3M(2048×1536) WDR(140dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m MicroSDmemory,IP67,IK10,PoE+	Call
		 IPC-HFW81230EP-Z	12Mega	1/1.7" 12Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 20fps@12M(4000×3000),25/30fps@4K(3840×2160) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC 4.1mm ~16.4mm motorized lens Max. IR LEDs Length 50m Micro SD memory,IP67,IK10,PoE+	79,500,000
Access ANPR Cameras		DH-ITC237-PW1B-IRZ	2Mega	Embedded with LPR algorithm inside the camera Support plate cutout, overview picture snapshot and video recording Embedded with White list database,control the barrier Powerful 2.7-12mm motorized lens and IR light, ideal for monitor ANPR distance as 3~8m Wide working temperature, IP67,IK10 True WDR technology Suitable for the ANPR detection and recognition in low speed environment (<20Km/h, for Australia and New Zealand), such as parking, access control and urban street.	65,200,000
Lite H.265 Series		IPC-HFW4631TP-ASE	2Mega	1/2.8" 6Megapixel progressive Starvis™ CMOS H.265 & H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens Max IR LEDs Length 60m IP67, IK10(optional), PoE+	23,000,000
Eco-savvy		IPC-HDW2431R-ZS	4Mega	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS]Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens, Max IR LEDs Length 50m, IP67, PoE	17,670,000
		DH-IPC-HFW5831EP-ZE	8Mega	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m Micro SD memory, IP67, IK10, PoE	46,060,000
Box Network		IPC-HF5431EP-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.264&H.265,25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2/1 Alarm in/out, 1/1 audio in/out(Built-in Mic) Auto back focus(ABF),Micro SD memory, PoE	Call
		IPC-HF8232FP	2Mega Starlight	1/1.9" 2Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 50/60fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Auto back focus(ABF), Micro SD memory, PoE	Call

Type	Picture	Model	Resolution	Main Features	IRR
Vari-focal Dome		DH-IPC-HDBW2231RP-VFS	2Mega	1/2.8" 2Megapixel progressive Starvis™ CMOS H.265 & H.264 dual-stream encoding 25/30fps@1080P(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens Max IR LEDs Length 30m IP67, IK10, PoE	17,980,000
Vandal Dome		IPC-HDBW1230EP-0360B-S2	2MP	1/2.7" 2M CMOS,ICR,H.264/MJPEG 25/30fps@1080P(1920x1080) Max IR LEDs length 30m 2.8mm fixed lens (3.6mm optional),IR 30m,IP67,IK10 DC12V/PoE	7,450,000
		IPC-HDBW1320EP-0360B-S3	3Mega	1/3" 3M CMOS,ICR,H.264/MJPEG 3MP(1~20fps),1080P(1~30fps) 3.6mm optional, IR 30m,IP67,IK10 DC12V/PoE	8,100,000
		IPC-HDBW1431EP-0360B	4Mega WDR	1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688x1520) &25/30fps@3M(2304x1296) 3.6mm fixed lens Max IR LEDs Length 30m IP67, PoE	11,900,000
EZ-IP		IPC-D1A30	3Mega	1/3" 3Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm optional) Max IR LEDs Length 30m IP67, IK10, PoE	7,500,000
		IPC-T1A20	2Mega	1/2.9" 2Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 25/30fps@2M(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6mm optional) Max IR LEDs Length 30m IP67, PoE	6,320,000
Long IR Range Eyeball		IPC-HDW4231E-AS-H	2Mega WDR	1/2.7" 2Megapixel progressive scan CMOS H.265 & H.264 & MJPEG triple stream encoding Max 25/30fps@2M(1920x1080) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens,IR LEDs Length 50m,IP67, PoE	9,520,000
		IPC-HDW4431EP-AS-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS Support H.264&H.265 dual codec 25/30fps@4M(2688x1520),Smart Detectionsupported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens (6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50mMicro SD memory, IP67, PoE	11,100,000










Telegram: @pouyacctv
Instagram: pouyacctv
www.pouyacctv.com

Type	Picture	Model	Resolution	Main Features	IRR
		IPC-HDBW2431RP-ZAS	4Mega WDR	1/3" 4M CMOS,ICR,WDR(120dB) H.265+/H.264/MJPEG,4MP(1~20fps),3MP(1~30fp) 2.7-12mm motorized lens IR 60m,Micro SD, IP67 DC12V/PoE	17,950,000
		IPC-HDBW5231EP-Z	2Mega WDR	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 50/60fps@1080(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 1/1 Alarm in/out, 1/1 audio in/out IR LEDs Length50m,Micro SD memory, IP67, IK10, PoE	29,000,000
		IPC-HDBW5431EP-Z-H	4Mega WDR	1/3" 4Megapixel progressive scan CMOS H.265&H.264,25/30fps@4Mp(2688x1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens 2/1Alarmin/out,1/1audioin/out Max. IR LEDs Length 50m,Micro SD memory, IP67, PoE	21,370,000

Eco-savvy		IPC-HDBW8232EP-Z	2MP Starlight WDR	1/1.9" 2Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 50/60fps@1080P(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 4.1mm ~16.4mm motorized lens Max.IRLEDsLength50m,MicroSDmemory,IP67,IK10,POE	Call
		IPC-HDBW8331EP-Z	3Mega WDR	1/2.8" 3Megapixel progressive scan STARVIS™ CMOS H.265&H.264,50/60fps@3M(2048x1536) WDR(140dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m MicroSDmemory,IP67,IK10,PoE+	Call
		IPC-HDBW81230EP-Z	12Mega	1/1.7" 12Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 20fps@12M(4000x3000),25/30fps@4K(3840x2160) 4.1mm ~16.4mm motorized lens Max. IR LEDs Length 50m Micro SD memory,IP67,IK10,PoE+	Call
		IPC-HDBW4631EP-ASE	6Mega	1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 30m Micro SD memory, IP67, IK10, PoE	23,700,000
	DH-IPC-HDBW5831EP-ZE	8Mega	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m Micro SD card memory, IP67,IK10, PoE+	46,060,000	









Type	Picture	Model	Resolution	Main Features	IRR
Speed Dome		SD49225T-HN	2Mega 25X	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom, Starlight technology Support H.265&H.264 Triple-streams encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P IVS, Support PoE+, IR distance up to 100m, IP66	53,600,000
		SD59225U-HNI	2Mega 25x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology, H.265 Encoding, Max. 50/60fps@1080P Auto-tracking and IVS, Support PoE+, IR distance up to 150m, IP66	49,200,000
		SD59230U-HNI	2Mega 30xStarlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 30x optical zoom Starlight technology H.265 Encoding, Max. 50/60fps@1080P Auto-tracking and IVS, Support PoE+ IR distance up to 150m, IP66	95,840,000
		SD59430U-HNI	4Mega 30X	1/3" 4Megapixel CMOS Powerful 30x optical zoom H.265 Encoding Max. 25/30fps@4M/3M, 25/30/50/60fps@1080P Auto-tracking and IVS Support PoE+, IR distance up to 100m IP66	113,300,000
		SD6C225U-HNI	2Mega 25x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology, H.265 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P Auto-tracking and IVS, IR distance up to 150m, IP66	Call
		SD6C430U-HNI	4Mega 30X	1/3" 4Megapixel CMOS Powerful 30x optical zoom, H.265 Encoding Max. 25/30fps@4M/3M, 25/30/50/60fps@1080P Auto-tracking and IVS, IR distance up to 100m, IP66	Call

Outdoor PTZ		SD6CE225U-HNI	2Mega 25x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology Max. 50/60fps@1080P Auto-tracking and IVS IR distance up to 200m Support PoE+, IP67, IK10	82,150,000
		PTZ1A225U-IRA-N	2Mega 25x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology H.265 Encoding Max. 50/60fps@1080P Auto-tracking and IVS Support PoE+ IR distance up to 150m IP67, IK10	74,700,000
		SD10A248V-HNI	2Mega 48X Starlight	1/1.9" 2Megapixel CMOS Powerful 48x optical zoom Starlight technology Max. 50/60fps@1080P Support Hi-PoE IR distance up to 450m, IP67	316,000,000
		SD6AE240V-HNI	2Mega 40x Starlight	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 40x optical zoom, Starlight technology H.265 Encoding, Max. 50/60fps@1080P Support Hi-PoE, IR distance up to 200m, IP67, IK10	198,000,000



Telegram: @pouyacctv
Instagram: pouyacctv
www.pouyacctv.com










Type	Picture	Model	Resolution	Main Features	IRR
Panoramic		IPC-PSD81602-A360	8x2MP Multi-Sensor Panoramic +PTZ Camera	Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS PTZ: One 1/1.9" 2Megapixel progressive scan CMOS H.265/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view Day/Night(ICR), 3DNR, AWB, AGC, BLC, Smart tracking Intelligent Function, Micro SD memory, IP67, IK10	Call
		IPC-PBW8601P	3x2 Mega	Three 1/2.8" 2Megapixel progressive scan STARVIS. CMOS H.265/H.264 triple-stream encoding Max 25/30fps@4096x832 Support 180-degree panoramic view Smart detection ,Intelligent Function Max. IR LEDs length 30m Micro SD memory, IP67, IK10, PoE+	Call
		DH-IPC-EBW8630P-IVC	6Mega	1/1.8" 6Megapixel progressive scan STARVIS™ CMOS H.265/H.264 triple-stream encoding Max 25/30fps@6M(3072x2048) Multiple dewarped Mode Day/Night(ICR), 3DNR, AWB, AGC, BLC > Smart detection Intelligent Function Max. IR LEDs length 10m Micro SD memory, IP67, IK10, PoE Panamorph Lens RPL: B4QQV	82,770,000
		IPC-EBW81200P	12Mega	1/2.3" 12Megapixel Exmor R CMOS H.264+/H.264 encoding Max 15fps@12M(4000x3000), 30fps@3M 1.57mm /F 2.2 lens Max> IR LEDs length 10m, Audio In/Out 1/1 Micro SD memory, IP67, IK10, PoE	Call






		IPC-EB5531P	5Mega	1/2.7" 5Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25fps@5MP(2592x1944), 25/30fps@3MP(2048x1520) Smart Detection supported WDR(120dB), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 1.4mm fixed lens Built-in Mic Micro SD memory, IP67, PoE	31,600,000
Pinhole		IPC-HUM8231-L1	4Mega	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS Day/Night(Electronic), WDR, 2.8mm Fixed Pinhole Lens 8-meters cable, Require a Main Box to work together	12,900,000
		IPC-HUM8231-E1		H.265&H.264 triple-stream encoding Support Smart H.265+/H.264+ 50/60fps@1080P(1920x1080) Day/Night(Electronic), WDR, 3DNR, AWB, AGC, BLC Smart detection Micro SD memory, PoE Multiple Lens Unit optional Require a Lens Unit to work together	45,700,000

PIR



Telegram: @pouyacctv
Instagram: pouyacctv
www.pouyacctv.com





Type	Picture	Model	Main Features	IRR
Compact 1U 1HDD		NVR2104HS-4KS2	4/8 Channel, H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback, HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	6,840,000
		NVR2108HS-4KS2		8,000,000
Compact 1U 1HDD		NVR4108HS-4KS2	8 Channel H.265/H.264 codec decoding, Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback, HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	15,970,000
Smart 1U 1HDD		NVR4116-4KS2	16 Channel, H.265/H.264 codec decoding Max 80Mbps Incoming Bandwidth, Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output, Up to 2ch@4K/8ch@1080P decoding	17,580,000
1U 2HDD		NVR4216-4KS2	16/32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding, Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback, HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	25,640,000
		NVR4232-4K-S2		28,080,000
		NVR4432-4K-S2		37,280,000
1U 2HDD		DHI-NVR4216-16P-4KS2	16/32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	45,980,000
		DHI-NVR4432-16P-4KS2		63,200,000
1U 2HDD		DHI-NVR5216-16P-4KS2	16Channel 1U 16PoE 4K&H.265 H.265+/H.265/Smart H.264+/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback, 1-8 PoE Ports Support 800m ePoE & EoC	56,420,000
1U 2HDD		NVR5224-24P-4KS2	24 Channel, Smart H.265+/H.265/Smart H.264+ codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback, HDMI/VGA simultaneous video output Support IPC UPnP, 24 PoE ports, 3D intelligent positioning with Dahua PTZ camera	89,100,000
1.5U 4HDD		NVR5432-4KS2	32 Channel, 4K&Smart H.265+/H.265/Smart H.264+ codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/2VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	62,500,000
1.5U 4HDD		NVR5464-4K-S2	64 Channel, H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera	79,000,000

2U 8HDD		NVR4832-4KS2	32 Channel 1U 4K&H.265 Lite Network Video Recorder H.265/H.264 codec decoding, Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback, HDMI/VGA simultaneous video output Support ANR technology to enhance the storage reliability when the network break down	66,500,000
		NVR5832-4KS2	32/64Channel 2U 4K&H.265 H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output, 3D intelligent positioning with Dahua PTZ camera	81,050,000
		NVR5864-4KS2		91,140,000
		NVR608-32-4KS2	384Mbps, Max 12MP, 16ch 1080P decoding, H.265/H.264, 1 VGA/2 HDMI(3840x2160), 2 RJ45(1000M), 4 USB(2USB3.0), 1/1ch audio in/out, 8 HDD(6TB each), 1 eSATA, 16/8 alarm in/out, fisheye dewarp, Smart Track, IVS(optional), face detection, RAID0/1/5/6/10/50/60, N+M, ANPR, thermal	91,180,000
	NVR608-64-4KS2	165,600,000		
16HDD		NVR616-64-4KS2	64Channel Ultra 4K H.265, Intel Processor Max 64/128 IP Camera Inputs, Max 384Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback, Supports RAID 0/1/5/10 iSCSI and Mini SAS for Expanded Storage Space, Smart Tracking and Intelligent Video	280,000,000






Telegram: @pouyacctv
Instagram: pouyacctv
www.pouyacctv.com

Type	Picture	Model	Main Features	IRR
4-Port PoE Switch (Unmanaged)		PFS3005-4P-58	Two-layer PoE Ethernet switch, MAC auto study and aging, MAC address list capacity is 1K, Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation., Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission, distance of power and network data is up to 250m.	Call
8-Port PoE Switch (Unmanaged)		PFS3110-8P-96	Two-layer industrial PoE switch, MAC auto study and aging, MAC address list capacity is 8K, Support IEEE802.3af, IEEE802.3at standard Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards, Industrial wide temperature design	Call
16-Port PoE Switch		PFS4218-16ET-240	Layer 2 management PoE switch, PoE budget: 240W Support PoE, PoE+, Hi-PoE, 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission, PoE management, PoE Setting/Event Statistics/Green PoE Search and upgrade via ConfigTool Support Web management, High lightning protection, design Non-blocking video transmission	Call
24-Port PoE Switch		PFS4226-24ET-360	Layer 2 management PoE switch, PoE budget: 240W Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300), 250 meters long distance PoE transmission, PoE management, PoE Setting/Event Statistics/Green PoE Search and upgrade via ConfigTool Support Web management, High lightning protection design Non-blocking video transmission	Call
PoE Extender		PFT1300	Support passive PoE cascade power supply and Ethernet data exchange able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m 1*RJ45 10/100M PoE power supply input; 1*RJ45 10/100M supply power for IP Cam; 1*RJ45 10/100M supply power for the next extender	Call
Ultra-HD Network Video Decoder		NVD0405DH-4K	H.265/H.264/MPEG4 video decoding 4ch@12M/4ch@4K/16ch@1080P/64ch@D1 decoding ability 1ch HDMI input, 4ch HDMI/VGA/BNC output, HDMI support Ultra HD 4K output Support up to 4 video-wall display units, support configuration of 1x1,2x1,2x2 Support audio, alarm, bi-directional talk, RS485	Call
Network Keyboard		NKB1000	Keyboard to Control, Dahua High Speed Dome, Dahua Standalone DVR Dahua Network High Speed Dome, Network Video Server Connection	Call
Tester		DH-PFM906	7" IPS HD retina capacitive touch screen(1920*1200);, Support IP, HDCVI/AHD/TVI/CVBS, SDI, Support HDMI Input/Output, Support PoE, DC12V 2A and USB5V 2A power out; Build-in 37Wh big capacity polymer lithium ion battery, Support TDR(network cable/coaxial cable), UTP cable tester and hunting, optical cable VFL, digital multi-meter function;; Support optical power meter test function	124,500,000
Junction Boxes		PFA121	HFWxxEZ/E Series Material: Aluminum IP66 Junction Box	1,600,000
		PFA134	HFWxxS, HFWxxT, HFWxxSL, HFWxxRM, HFWxxR Series Material: Aluminum, IP66 Junction Box	670,000
		PFA135	HFWxxR-Z/VF, HFWxxB, HFWxxD Series Material: Aluminum IP66 Junction Box	530,000
		PFA137	HDBWxxR-Z/VF, HDWxxR-Z, SD22 Series Material: Aluminum IP66 Junction Box	670,000

		PFA139	HDBWxxF , HDWxxEM Series Material: Aluminum IP66 Junction Box	730,000
		PFA152-E	PFB203W,PFA121,PFA134,PFA135,PFA137+ PFA152-E Pole mount Material: Aluminum	2,140,000
		PFB730W	"PTZ1A225U-IRA-N" Material: Aluminum Wall Mount Bracket	4,300,000
Wall Mount		PFB203W	HDBWxxR-Z/VF/E/F,HDWxxR-Z/VF/EM/E/S ,EB Material: Aluminum Wall Mount Bracket	940,000



Telegram: @pouyacctv
Instagram: pouyacctv
www.pouyacctv.com

Type	Picture	Model	Main Features	IRR
Lens		PLZ1040-D	Focal length:2.7-12mm Aperture:F1.6 Focus:Manual Zoom:Manual Iris:DC-Iris	Call
		PLZ20C0-D	Focal length:3.7-16mm Aperture:F1.5 Focus:Manual Zoom:Manual Iris:DC-Iris	Call
		PLZ21C0-P	Focal length:10.5-42mm Aperture:F1.5 Focus:Manual Zoom:Manual Iris:DC-Iris	Call